

Angle grinder DCG 125-S



Applications

- Cutting and grinding mineral materials
- Masonry
- Brick
- Natural stone
- Metal surfaces
- Concrete slabs

Advantages

- Angle grinder for cutting and grinding on mineral materials
- Hilti Smart Power Technology™ for constantly high cutting performance
- Hilti ATC Active Torque Control technology minimizes undesirable kick-back
- Time-saving cutting and slitting (chasing) in widths up to 25 mm using two discs (with DC EX 125/5" accessories)
- Non-slip grip area on the back of the tool and soft-grip side handle for low vibration and maximum safety
- Restart interlock









Technical data	
Rated input power	1400 W
Triaxial vibration value for angle grinding (ah,AG) ¹⁾	4.6 m/s ²
A-weighted emission sound pressure level ²	90 dB (A)
Weight according to EPTA Procedure 01/2003	2.4 kg
No-load speed	11000 rpm
Disc diameter	125 mm
Max. cutting depth	35 mm
Smart power	Yes
Spindle thread	14 mm
Active Torque Control	Yes

¹⁾ according to EN 60745-2-3

²⁾ according to EN 60745



Order description	Package contents	Sales pack quantity	Item number
DCG 125-S 240V box	1x Angle grinder DCG 125-S 230V GB	1 pc	382579

Please visit our website for the latest item numbers and related products.